

								
	Piccolo STX	Piccolo Hybrid	Piccolo Plus	Piccolo ATX - Battery Operated	Piccolo ATX - Solar	Piccolo ATX - Rechargeable	Piccolo TMX	RF Tag
Size	85x52x25.4	100x58x30	100x58x30	132x82x34	132x82x35	132x82x36	100x58x30	33X65X15.5
Weight	94g	110g (w/o cable)	110g (w/o cable)	170g	170g	170g	110g (w/o cable)	20g
Inclusive in Base Unit								
IP Standard	Flame retardant ABS/PC	IP65	IP65	IP67	IP67	IP67	IP65	IP67
GPS	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	X
Cellular GSM/GPRS	GSM/GPRS or EDGE/HSPA+ (3G)	GSM/GPRS or EDGE/HSPA+ (3G)	GSM/GPRS or EDGE/HSPA+ (3G)	GSM/GPRS or EDGE/HSPA+ (3G)	GSM/GPRS or EDGE/HSPA+ (3G)	GSM/GPRS or EDGE/HSPA+ (3G)	GSM/GPRS or EDGE/HSPA+ (3G)	X
Integrated rechargeable lithium battery and charger	Option	YES	Option	X	YES(2)	YES(2)	YES	X
I/O	3 digital in 2 digital out 1 analog in	2 digital in 1 digital out 1 analog in	3 digital in 2 digital out 1 analog in	X	X	X	X	X
Internal Temp. Sensor	YES	YES	YES	YES	YES	YES	YES	
Options								
IO add on Options	X		3 additional IO's for a total of 6	One digital input including waterproof connector. Might be normally open or normally closed (alarm link)	One digital input including waterproof connector. Might be normally open or normally closed (alarm link)	One digital input including waterproof connector. Might be normally open or normally closed (alarm link)		Option - Untegreted temperature sensor , External IO ,

	 Piccolo STX	 Piccolo Hybrid	 Piccolo Plus	 Piccolo ATX - Battery Operated	 Piccolo ATX - Solar	 Piccolo ATX - Rechargeable	 Piccolo TMX	 RFTag
CAN Bus, J1939 and J1708	Option	X	Option	X	X	X	X	X
ODBI connector pre-wired	Option	X	Option	X	X	X	X	X
Non intrusive J1939 connector	Option	X	Option	X	X	X	X	X
Accelerometer packaged with driver behavior with external buzzer	Option	Option	Option	X	X	X	X	X
Driver ID Key Dashboard Unit	Option	Option	Option	X	X	X	X	X
Driver ID (Dallas key)	Option	Option	Option	X	X	X	X	X
Integrated rechargeable lithium battery and charger	Option	Standard (1)	Option	X	Standard (2)	Standard (2)	Standard (1)	X
Additional rechargeable Lithium battery	Option	Option- add on 1 (For a total of 2)	Option	X	Option- add on 2 (For a total of 3)	Option- add on 1 (For a total of 3)	Option- add on 1 (For a total of 2)	X
Vibration Sensor	Option	Standard	Option	Standard	Standard	Standard	Standard	X
External Temp. Sensor	Option - 1 sensor	Option - Up to 6 sensors in parallel 3 meter each	Option - Up to 6 (Piccolo plus - 15 meter for two sensors + 4 sensors not more than 3 meters)	X	X	X	Standard - 1 * Digital +/- 0.5 accuracy Option up to 8	1 Optional
External buzzer installed on the wire harness	Option	X	Option	X	X	X	X	X
Internal Buzzer	X	X	Option	X	X	X	X	X

	 Piccolo STX	 Piccolo Hybrid	 Piccolo Plus	 Piccolo ATX - Battery Operated	 Piccolo ATX - Solar	 Piccolo ATX - Rechargeable	 Piccolo TMX	 RFTag
External Dual magnetic GPS & Cellular antenna including SMA connectors	Option	X	Option	Option	Option	Option	X	X
3G	Option	Option	Option	Option	Option	Option	Option	X
Internal cellular antenna and external GPS antenna	X	X	Option	Option	Option	Option	X	X
Cigarette plug and cable for portability	Option	X	Option	X	X	X	X	X
Garmin Interface	X	X	Option	X	X	X	X	X
Starter Killer	Option	Option	Option	X	X	X	X	X
WIFI	X	X	Option	X	X	X	X	X
Bluetooth	X	X	Option	X	X	X	X	X
Active RFID	X	X	Option	X	X	X	X	X
Passive RFID	X	X	Option	X	X	X	X	X
RS-232	X	X	Option	X	X	X	X	X