

G100

Modular and expandable telematics device with Flexi-Card slot



APPLICATIONS




Vehicle and
Fleet Tracking



Lone and
Remote
Workers



Out of cellular
coverage
locations



Cold Chain
Management



Agricultural
Vehicles and
Sites



Mining, Oil
and Gas Rigs

The G100 is a highly capable GPS/GLONASS cellular tracker with a variety of inputs and outputs. The Flexi-Card slot sets it apart, providing endless integration and expansion possibilities

FEATURES

- 24/7 Vehicle location
- Cellular data when in coverage
- Iridium satellite out of cell coverage (option)
- Man Down Pendant (option)
- Iridium, Wi-Fi, RF (Flexi-Card options)
- Ignition + 4 Inputs and 2 Outputs
- Driver ID: RFID and iButton
- PLC interfaces: RS232 and RS485
- 3D Accelerometer
- Internal Back-up Battery

MECHANICAL FEATURES

Snap-Clip ABS Plastic Housing	Housing clips together for easy assembly
-------------------------------	------------------------------------------

Operating temperature	-20°C to +60°C
-----------------------	----------------

Dimensions (mm)	L 125 x W 65 x H 30
-----------------	---------------------

Weight	250 grams including battery
--------	-----------------------------

Automotive Power	8-45V DC
------------------	----------

CONNECTIVITY

Cellular	2G/3G (Various Global Bands)
----------	------------------------------

SIM	SIM holder for standard Cellular SIM card (2FF size)
-----	------------------------------------------------------

GPS and Cellular Antenna	Internal antennas tuned by RF laboratories to ensure optimal performance
--------------------------	--------------------------------------------------------------------------

GPS TRACKING

GPS Module	U-Blox Max8 GPS, High sensitivity assisted GPS receiver, 72 channel (-167dBm)
------------	-------------------------------------------------------------------------------

AssistNow Offline	Predicts satellite locations Reduces the time to first fix Improves performance in "urban canyons"
-------------------	----------------------------------------------------------------------------------------------------------

Antenna with LNA	Boosted by low-noise amplifier (LNA) allows operation in "urban canyons"
------------------	--------------------------------------------------------------------------

SPECIFICATIONS

Recovery Mode	Switch from Daily Locate to Live Tracking over-the-air
---------------	--------------------------------------------------------

Auto-APN	Analyse SIM and detect APN from pre-loaded list
----------	-------------------------------------------------

3D Accelerometer	3 axis accelerometer intelligently reports on harsh driving and suspected accident events, as well as harsh braking, acceleration and cornering
------------------	-------------------------------------------------------------------------------------------------------------------------------------------------

G-Force Events	Accident and Rollover Accident Data (Black Box) Harsh Acceleration, Braking and Cornering
----------------	-------------------------------------------------------------------------------------------------

Driver ID	Driver Identification with RFID or iButton (Keyfobs) Driver Lists on device
-----------	--------------------------------------------------------------------------------

Inputs and Outputs	5 x Digital Inputs configurable over-the-air 2 x Switched Ground Digital Outputs
--------------------	-------------------------------------------------------------------------------------

Interfaces	iButton, RS232, DMCAN, 5V Out
------------	-------------------------------

FLEXI-CARD SLOT

Iridium Satellite	Auto-switch cellular/iridium When out of GSM coverage, important data reported via Iridium
-------------------	-----------------------------------------------------------------------------------------------

Wi-Fi, RF Gateway, RS485, PT100, I ² C, 2 x Analogue	
-----------------------------------------------------------------	--

Flexi-Card IO	6 external wires connected to the Flexi-Card
---------------	----------------------------------------------